

### Battery Lead Assembly:

Provides connection from heater to portable power source for heater models requiring 12 volt electric start. Cable length must be selected to ensure power source is located in an area classified as General Purpose.

975-001	25' Battery Lead Assy 10ga. c/w 3/4" NPT strain relief connector
975-001-2	25' Battery Lead Assy 10ga. c/w 1/2" NPT strain relief connector
975-001(SP30)	30' Battery Lead Assy 10ga. c/w 3/4" NPT strain relief connector
975-001(SP40)	40' Battery Lead Assy 10ga. c/w 3/4" NPT strain relief connector
975-001-2(SP30)	30' Battery Lead Assy 10ga. c/w 1/2" NPT strain relief connector
975-015	25' Battery Lead Assy 14ga. c/w 3/4" NPT strain relief connector (S12-12 ↘)
975-015-2	25' Battery Lead Assy 14ga. c/w 1/2" NPT strain relief connector (S12-12 ↘)
975-015(SP30)	30' Battery Lead Assy 14ga. c/w 3/4" NPT strain relief connector (S12-12 ↘)
975-015-2(SP30)	30' Battery Lead Assy 14ga. c/w 1/2" NPT strain relief connector (S12-12 ↘)



### Vent Hood Assembly:

Expels excess water vapor, created as a by-product of the catalytic process, to the exterior of the building.

977-018	8" Vent Hood Assembly (S8-8)
977-019	12" Vent Hood Assembly (S12-12,12-24)
977-020	24" Vent Hood Assembly (S12-24,24-24)
977-021	36" Vent Hood Assembly (S12-36,18-36)
977-022	18" Vent Hood Assembly (S18-36,18-48,18-60)
977-023	48" Vent Hood Assembly (S12-48,18-48,24-48)
977-024	60" Vent Hood Assembly (S12-60,18-60,24-60)



#### Vent hood assembly includes:

- hood - 3" x 36" pipe\*
- 3" cap - 3" elbow\*
- 8" flashing

\* Extra pipe, elbows available

### Portable Stand Assembly:

Provides stable support for heaters in portable applications. Typically used with 12 volt electric start models.

990-007	Portable Stand Assembly (S12-24, S12-36, S24-24 heater models)
990-009	Portable Stand assembly complete with Cable Hanger (S12-24, S12-36, S24-24 heat models)

Custom Portable Stand Assemblies available, Contact our Calgary Factory.



### CGA Gas Hose Assembly:

Provides a means to connect heaters to the fuel supply connection. Typically used with portable heaters.

993-002	10 ft CGA Gas Hose Assembly, 350 PSI rating, 1/4" male NPT fixed connection X 1/4" male NPT swivel connection
993-002SP	30 ft CGA Gas Hose Assembly, 350 PSI rating, 1/4" male NPT fixed connection X 1/4" male NPT swivel connection

Other length and size hoses available. Contact our Calgary Factory.



### Miscellaneous:

590-001	NG to LP fuel Conversion Kit
590-002	LP to NG fuel Conversion Kit
590-007FE	Fuel Orifice (Farris)
590-008	Fuel Orifice – 5/16" hex
590-009	Fuel Orifice – 7/16" hex

When ordering Conversion Kits or Fuel Orifices it is necessary to provide our Calgary Factory with the Make, Model, Serial Number and Fuel of the heater being converted.



### Protective Grills:

Provides protective barrier to prevent damage to the heater catalyst and injury to personnel.

260-029	SR-8
260-030	SR-12
260-032	S6-6
260-032	S6-12
260-032	S6-24
260-034	S12-12
260-035	S12-24
260-035-2	S24-24
260-036	S12-36
260-037	S12-48
260-038	S12-60
260-039	S18-36
260-040	S18-48
260-041	S18-60
260-042	S24-48
260-043	S24-60



### Pressure Regulators:

Properly selected regulators reduce fuel supply pressure to within acceptable operating limits of downstream devices.

701-011	1/4" NPT X 1/4" NPT, 6,000 PSI maximum inlet,	0 - 150 PSI outlet	High Pressure Regulator	
701-022	1/4" NPT X 1/4" NPT,	250 PSI maximum inlet,	11" WC outlet	912 Regulator
912-101	1/4" NPT X 3/8" NPT,	250 PSI maximum inlet,	11" WC outlet	912 Regulator



### Thermostats:

Thermostats are self contained mechanical temperature control devices equipped with an adjustable set point dial. They are used to monitor ambient or equipment temperature and act to regulate heater fuel supply from minimum to maximum values as required. All thermostats are factory adjusted for a specific heater size, specific fuel type and heater's rated fuel pressure. Do not interchange with other heater sizes, fuel types or pressures.

777-015	1/2" NPT Thermostat, 1/2 PSI maximum inlet
777-029	3/8" NPT Thermostat, 1/2 PSI maximum inlet
777-025	3/8" NPT Tube Connection Thermostat, 1/2 PSI maximum inlet



### Wall Mount Brackets:

Brackets facilitate mounting heaters for optimum heating effect.

980-003	12" Wall Mount Bracket Assembly (S12-24, S12-36, S24-24)
980-002	18" Wall Mount Bracket Assembly (18" heaters models)
980-010	24" Wall Mount Bracket Assembly (24" heaters models)
980-013	6" Wall Mount Bracket Assembly (6" heaters models)

Custom Wall Mounts also available, contact our Calgary Factory.

